

Main Features

| | | DLA-NZ900 | DLA-NZ800 | DLA-NZ700 | DLA-NZ500 |
|---------------------------------|---|--------------------------------|-----------|--|-----------|
| 8K/e-shiftX (4-direction shift) | | ✓ | ✓ | - | - |
| 8K60p Input | | ✓ | ✓ | - | - |
| 4K120p input | | ✓ | ✓ | - | - |
| 4K60p input | | ✓ | ✓ | ✓ | ✓ |
| Lens Diameter | | 100 mm | 65 mm | 80 mm | 80 mm |
| Light Source | | New Blu-Escent Laser | | | |
| Light Source Control | | 101 steps | | | |
| Brightness | | 3,300 lm | 2,700 lm | 2,300 lm | 2,000 lm |
| 0.69-inch 4K D-ILA Device | | ✓ | ✓ | ✓ | ✓ |
| Ultra-High Contrast Optics | | ✓ | ✓ | ✓ | ✓ |
| Contrast Ratio | Dynamic | | ∞:1 | | |
| | Native | 150,000:1 | 100,000:1 | 80,000:1 | 40,000:1 |
| Cinema Filter (DCI-P3) | | ✓ | √ | ✓ | - |
| HDR | HDR10+ | ✓ | ✓ | ✓ | ✓ |
| | HLG | ✓ | ✓ | ✓ | ✓ |
| | Mastering Info Display | ✓ (Max CLL/Max FALL/DML) | | | |
| | Frame Adapt HDR Generation 2 | ✓ | ✓ | ✓ | ✓ |
| | Frame Adapt HDR Generation 2 Deep Black Mode | ✓ | ✓ | ✓ | ✓ |
| | Theater Optimizer | ✓ | ✓ | - | - |
| | FILMMAKER MODE™ | ✓ | ✓ | ✓ | ✓ |
| "Vivid" Mode for SDR | | ✓ | ✓ | ✓ | ✓ |
| 3D Support | | ✓ | ✓ | - | - |
| MPC (Multiple Pixel Control) | | ✓ | ✓ | ✓ | ✓ |
| Clear Motion Drive | | ✓ | √ | ✓ (black frame insertion at 60Hz input only) | |
| Motion Enhance | | ✓ | ✓ | - | - |
| Low Latency Mode | | ✓ | ✓ | - | - |
| Color Management | | √ 6-axis | | | |
| Auto Calibration | | ✓ | ✓ | ✓ | ✓ |
| Installation Mode | | √ (10 memories) √ (5 memories) | | | emories) |
| isfccc Certification | | ✓ | ✓ | ✓ | ✓ |
| Screen Adjustment Mode | | ✓ | ✓ | ✓ | ✓ |
| Keystone | | √Vertical Keystone | | | |
| Anamorphic | | ✓ | ✓ | ✓ | ✓ |
| USB Back-up | | ✓ | ✓ | ✓ | ✓ |

©JVCKENWOOD Corporation MF-nz9480