

UHZ35

Eco-friendly compact high brightness 4K UHD laser projector



- **Incredible True 4K UHD resolution and laser technology - HDR and HLG compatible**
- **Lights on viewing - bright 3500 lumens - Perfect for big screen home entertainment and immersive gaming**
- **Small form factor for easy installation - 1.6x zoom, 360-degree and portrait projection**
- **Lightning-fast gaming - Supports 1080p 240Hz at 4.4ms and 4K 60Hz at 17ms**



The UHZ35 is one of Optoma's most compact and hassle-free 4K UHD DuraCore laser projectors to date. Designed for maintenance-free continuous operation, it delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.¹

An added benefit, the UHZ35 features an external power supply offering more reliability, portability and energy efficiency.

Specifications

UPC: 796435 81 542 4, EAN: 5055387668898, Colour: White



Display/image

| | |
|----------------------------------|------------------------------------|
| Display technology | DLP® |
| Resolution | UHD (3840x2160) |
| Brightness | 3,500 lumens |
| Contrast ratio | 500,000:1 |
| Native aspect ratio | 16:9 |
| Aspect ratio - compatible | 4:3, 16:9, 16:10 |
| Keystone correction - horizontal | +/-30° |
| Keystone correction - vertical | +/-30° |
| Displayable colours (millions) | 1073.4 |
| Horizontal scan rate | 15 ~ 140Khz |
| Vertical scan rate | 24 ~ 240Hz |
| Uniformity | 80% |
| Screen size | 0.66m ~ 7.7m (26" ~ 303") diagonal |

Lamp info

| | |
|-------------------|--------------|
| Light source type | Laser |
| LASER life | 30,000 hours |

Optical

| | |
|-------------------------|----------------|
| Throw ratio | 1.4:1 ~ 2.24:1 |
| Projection distance (m) | 1.3m - 9.4m |
| Zoom | 1.6 |
| Zoom type | Manual |
| Focal length (mm) | 20.91 ~ 32.62 |
| Native offset | 116% |

Connectivity

| | |
|-------------|---|
| Connections | Inputs 1 x HDMI 2.0, 1 x HDMI 2.0 (eARC) Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RJ45, 1 x RS232 |
|-------------|---|

General

| | |
|--------------------------|--|
| Noise level (min) | 28dB |
| Noise level (max) | 35dB |
| PC compatibility | UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| 2D compatibility | NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) |
| 3D compatibility | Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) |
| 3D | Full 3D |
| Security | Security bar, Kensington Lock, Password protected interface |
| IP rating | IP6X |
| OSD / display languages | 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese |
| 24/7 operation | Yes |
| 360° operation | Yes |
| Operating conditions | 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10,00ft |
| Remote control | Card style |
| Speaker count | 1 |
| Watts per speaker | 15W |
| In the box | AC power cord Remote control with 1x CR2025 Battery Basic user manual |
| Input lag | 4.40ms |
| Optional wireless models | UHDCast Pro |

Power

| | |
|-----------------------------|---|
| Power supply | External power supply, 100V ~ 240V, 50-60Hz |
| Power consumption (standby) | <0.5W |
| Power consumption (min) | 126W |
| Power consumption (max) | 185W |

Weight and dimensions

| | |
|---------------------------|-----------------|
| Dimensions (W x D x H) mm | 274 x 216 x 114 |
| Gross weight | 4.2 kg |
| Net weight | 3 kg |