4-in/4-out USB 2.0 MIDI Interface



User's Guide



ESI M4U XT

Introduction


Thank you for choosing the ESI M4U XT.

M4U XT is a convenient 4-in / 4-out USB 2.0 MIDI interface with 64 channels for PC and Macintosh systems. With M4U XT you can obtain perfect MIDI timing and performance at an extremely affordable price.

Features


- 4-in / 4-out MIDI interface (64 MIDI channels)
- perfect MIDI timing
- high-speed connection to USB-equipped computer (USB 2.0 and
- USB 1.1 compatible)
- MIDI-activity indicators for each port
- bus powered, requires no external power supply
- compact 1/3 rack size
- no driver needed for Windows XP, Windows Vista, Windows 7, Windows 8, Windows 10. Linux and Mac OS X

Front Panel



The front panel of M4U XT has 4 indicator LEDs for the 4 MIDI inputs and 4 indicator LEDs for the 4 MIDI outputs on the left side. These LEDs will flash on activity of the corresponding MIDI port. In the middle, there is one MIDI output port (labeled OUT 4). On the right are three MIDI inputs (labeled IN 2, IN 3 and IN 4).

Rear Panel



The rear panel features three MIDI outputs (labeled OUT 1, OUT 2 and OUT 3) and one MIDI input (labeled IN 1). On the right is the USB port that is used to connect M4U XT to the USB port of your computer via the supplied cable.

Installation

Find the USB port on your computer. Make sure your computer is switched on. Connect the supplied USB cable between the connector on the back of M4U XT and the USB port on your computer. No driver installation is needed.

ESI M4U XT

Under Windows XP, you can check if M4U XT has been installed correctly, by going to *Control Panel > Sounds & Multimedia > Audio > MIDI Playback*. You will see 4 new USB MIDI entries in the MIDI port selection. Note that this dialog does not exist under Windows Vista, Windows 7 or Windows 8. Please start your MIDI application (like a sequencer or notation software) to check the MIDI ports there.

Under Mac OS X, you can launch the *Audio MIDI Setup* application. M4U XT will be listed under MIDI Devices with 4 I/O ports.

General Information

Trademarks: ESI, M4U and M4U XT are trademarks of ESI Audiotechnik GmbH. Windows is a trademark of Microsoft Corporation. Other product and brand names are trademarks or registered trademarks of their respective companies.

Correspondence: For technical support inquiries, contact your nearest dealer, local distributor or ESI support online at www.esi-audio.com.

Disclaimer: All features and specifications subject to change without notice. Parts of this manual are continually being updated. Please check our web site www.esi-audio.com occasionally for the most recent update information.