

LIVE TO PLAY LIVE®





# M169 CARBON COPY® ANALOG DELAY

#### DESCRIPTION


- 100% analog bucketbrigade technology
- Up to 600ms of delay with switchable modulation
- Internally adjustable modulation circuit
- True bypass

## **POWER**

The MXR Carbon Copy Analog Delay is powered by one 9-volt battery (remove bottom plate to install), a 9-volt AC Adapter such as the Dunlop ECB003/ECB003EU or a DC Brick™ power supply.

## **CONTROLS**

- MOD switch toggles modulation on/off (blue LED indicates on)
- 2 REGEN knob sets number of repeats
- 3 MIX knob controls blend of wet and dry signals
- 4 DELAY knob sets delay time
- FOOTSWITCH toggles effect on/bypass (blue LED indicates on)



#### **DIRECTIONS**

- Run a cable from your guitar to the Carbon Copy's INPUT jack and another cable from the Carbon Copy's OUTPUT jack to your amplifier.
- Start with all controls at 12 o'clock.

SAMPLE SETTINGS

- Turn the effect on by depressing the footswitch.
- Rotate the REGEN knob clockwise to increase the number of repeats or counterclockwise to decrease it.
- Rotate the MIX knob clockwise to increase the ratio of wet to dry signal or counterclockwise to decrease it. Fully clockwise results in 100% wet signal while fully counterclockwise results in 100% dry signal.
- Rotate the DELAY knob clockwise to increase delay time or counterclockwise to decrease it.
- Push in the MOD switch to add modulation to your delay signal. Modulation width and speed can be adjusted internally with a 2mm slotted screwdriver (see Diagram A).

#### DIAGRAM A

MODULATION

WIDTH S SPEED

MEMPHIS SLAP	GOLDEN AGE GUITAR GOD	SKANK'N DUB
MOD MIX DELAY	MOD MIX DELAY	MOD MIX DELAY

### **SPECIFICATIONS**

Input Impedance Output Impedance	1 MΩ 1 kΩ
Max Input Level	+5 dBV at 500 Hz
Max Output Level	+8 dBV
Noise Floor*	
Mix at Max CW	-96 dBV
Mix at Max CCW	-104 dBV
Delay Distortion	<1% at 1 kHz,
	-5 dBV Input
Delay Time	20 ms to 600 ms
Noise Reduction	2:1 ratio
Modulation Speed	0.2 Hz to 2.2 Hz
Bypass	True Hardwire
Current Draw	26 mA
Power Supply	9 volts DC

<sup>\*</sup>Regen at max CCW, A-weighted



DUNLOP MANUFACTURING, INC. P.O. BOX 846 BENICIA, CA 94510 U.S.A. TEL: 1-707-745-2722 FAX: 1-707-745-2658