

# **BR** *LOUDSPEAKERS*



 **YAMAHA**

ive BR models are designed to fit the budgets of performing musicians, small churches, and schools while delivering the full-frequency response and high output of more costly systems. Although their "BR" prefix was chosen to represent "bass reflex," it also proves very appropriate for describing the line's advanced feature set...

**Built Right...**Combining our knowledge of acoustics and advanced computer controlled woodworking, Yamaha Music Manufacturing in Thomaston, Georgia, crafts the BR line of sound reinforcement loudspeakers. This world class, environmentally friendly, ISO 14001-registered facility carefully assembles each cabinet to exacting tolerances. Each model's large steel handle(s), corner protectors, and built-in pole socket assure both durability and flexibility.

**Better Response...**BR cabinets are carefully designed for the best balance of small, easy to handle size and great low-frequency response, using Bass Reflex technology. High-frequency response is also enhanced with a new titanium HF driver and 90° by 40° non-resonant horn.

**Best Reliability...**All BR-Series models are covered by a three-year warranty. With integral protection circuitry built into the passive crossover, you can expect a long life of high output and minimal distortion.

Whichever model you choose, your message is sure to be heard using BR-Series loudspeakers...and you can take the savings to the bank!

## THE NEW BR-SERIES FROM YAMAHA COMBINES AFFORDABILITY WITH HIGH PERFORMANCE



### BR10

Woofer .....	10"
Tweeter (diaphragm) .....	1" Titanium
Frequency Response (-10dB) .....	.65Hz-20kHz
Power Handling (noise*/program/peak) .....	125/250/500
* EIA RS426	
Nominal Impedance .....	.8 ohms
Sensitivity 1W, 1m .....	96dB
Input Connectors .....	2 X 1/4" Phone
Dimensions W x H x D (approximate) .....	14 3/4" x 21" x 12 3/4"
Weight (lbs.) .....	31.5




### BR12

Woofer .....	12"
Tweeter (diaphragm) .....	1" Titanium
Frequency Response (-10dB) .....	.65Hz-20kHz
Power Handling (noise*/program/peak) .....	150/300/600
* EIA RS426	
Nominal Impedance .....	.8 ohms
Sensitivity 1W, 1m .....	97dB
Input Connectors .....	2 X 1/4" Phone
Dimensions W x H x D (approximate) .....	15 3/4" x 22 1/2" x 13 1/4"
Weight (lbs.) .....	35.2




### BR15


Woofer .....	15"
Tweeter (diaphragm) .....	1" Titanium
Frequency Response (-10dB) .....	.60Hz-20kHz
Power Handling (noise*/program/peak) .....	200/400/800
* EIA RS426	
Nominal Impedance .....	.8 ohms
Sensitivity 1W, 1m .....	98dB
Input Connectors .....	2 X 1/4" Phone
Dimensions W x H x D (approximate) .....	19" x 25 3/4" x 14 1/2"
Weight (lbs.) .....	46.9



Steel corner protectors keep your cabinets free from dings and damage associated with frequent transport.



Large metal handles mounted at each cabinet's center of gravity make them very easy to carry.



All models, including the monitors, come with stand/pole sockets for flexibility of use.



### BR12M

Woofer .....	12"
Tweeter (diaphragm) .....	1" Titanium
Frequency Response (-10dB) .....	.65Hz-20kHz
Power Handling (noise*/program/peak) .....	150/300/600
* EIA RS426	
Nominal Impedance .....	.8 ohms
Sensitivity 1W, 1m .....	97dB
Input Connectors .....	2 X 1/4" Phone
Dimensions W x H x D (approximate) .....	22 1/2" x 16" x 13 1/4"
Weight (lbs.) .....	34.3



A large non-resonant, constant-directivity horn provides even 90° X 40° high-frequency dispersion.



### BR15M

Woofer .....	15"
Tweeter (diaphragm) .....	1" Titanium
Frequency Response (-10dB) .....	.60Hz-20kHz
Power Handling (noise*/program/peak) .....	200/400/800
* EIA RS426	
Nominal Impedance .....	.8 ohms
Sensitivity 1W, 1m .....	98dB
Input Connectors .....	2 X 1/4" Phone
Dimensions W x H x D (approximate) .....	25 3/4" x 19 1/4" x 14 1/2"
Weight (lbs.) .....	46



Specifications subject to change without notice  
Yamaha Corporation of America 6600 Orangethorpe Avenue, Buena Park, CA 90620 [www.yamaha.com/proaudio](http://www.yamaha.com/proaudio) © 2004

Manufactured in an environmentally friendly facility

