

d:dicate™ MMP-A Microphone Preamplifier

Ultra transparent transformerless Preamplifier with active drive for impedance balancing. Combine this Preamplifier with any Microphone Capsule in the d:dicate™ Recording Microphone series.

Attenuation pad

The MMP-A Preamplifier has a 20 dB attenuation push-switch at the XLR connector. Use a pencil or the like to activate the attenuator and lower the output by 20 dB.



d p a microphones.com / MMP-A

Service & repair

If you are not satisfied with the characteristics exhibited by this product, please go to www.dpamicrophones.com/service for instructions.

Warranty

The d:dicate™ MMP-A Microphone Preamplifier is covered by a five-year limited warranty.

CE marking

This product conforms to all relevant directives approved by the European Commission.

Specifications

Output connector

XLR-3M. Pin 1: shield, Pin 2: signal + phase, Pin 3: - phase

Switchable attenuator

0 dB / -20 dB

Output impedance

< 200 Ω

Current consumption

2.8 mA

Output balance principle

Impedance balancing with Active Drive

Common Mode Rejection Ratio (CMRR)

> 60 dB

Power supply (for full specifications)

48 V Phantom power (± 4 V)

Weight

149 g (4.9 oz)

Operating temperature range

-40 to 45°C (14 to 113°F)

Relative humidity

Up to 90%