

HK Audio Linear 5 Rock Pack - Specifications

HK Audio Linear 5 L5 112 FA 12" Active Speaker

- **Maximum SPL:** 127dB half space (at 10 percent THD)
 - **Peak:** 135dB half space (at 10 percent THD)
 - **Calculated:** 137dB half space
- **Frequency Response:**
 - **+/-3dB:** 64Hz - 18kHz
 - **-10dB:** 57Hz - 20kHz
- **Power Rating:** 1000W
- **Amplifier:** Class-D, bi-amped
- **Active Protection Circuits:**
 - Undervoltage protection
 - Thermoprotection
 - Short-circuit protection
 - Overcurrent protection
 - Subsonic filter, 24db/oct
 - Peak limiter
- **Low/Mid Speaker:** 1 x 12"
- **HF Driver:** 1"
- **Horn:** 60° - 90° (asymm) x 55° CD horn, rotatable
- **Cut-off Frequency Active:** 1.65kHz, 24dB/oct
- **Connections:**
 - 2 x XLR-1/4" combo IN
 - 2 x XLR THRU
 - 1 x XLR mix OUT
- **Input Sensitivity:** +4dBu at gain centreclick / L5 system level
- **Sensitivity Switch:** Line/Mic input A
- **Equalizer:** EQ switch
 - Small Venue / High Power
- **Pole Mount:** DuoTilt 3/7
- **Rigging Points:** 3 x M8
- **Handles:** 2 x integrated
- **Enclosure:** Hybrid (birch multiplex / MDF)
- **Grille:** 2mm metal grille backed with black acoustic foam
- **Finish:** Acrylic enamel, black
- **Dimensions:** 370mm x 670mm x 365mm (W x H x D)
- **Weight:** 23.9kg / 52.7lbs

HK Audio Linear L SUB 1200 A 2 x 10" Active Subwoofer

- **Maximum SPL:** 126dB half space (at 10 percent THD)
 - **Peak:** 128dB half space (at 10 percent THD)
 - **Calculated:** 129dB half space
- **Frequency Response:**
 - **+/-3dB:** 55Hz - X-over
 - **-10dB:** 38Hz - X-over
- **Power Rating:** 1200W
- **Amplifier:** Class-D
- **Active Protection Circuits:**
 - Under-voltage
 - Thermal
 - Short circuit
 - Over-current
 - Subsonic filter, 24dB/oct

- Peak limiter
- **Low-Frequency Speaker:** 2 x 10" (with advanced cooling technology)
- **Cut-Off Frequency Active:** 110/130Hz variable with 24dB/oct
- **Connections:**
 - 2 x XLR combo inputs (balanced)
 - 2 x XLR thru (balanced)
 - 2 x XLR mid/high out
 - 1 x SpeakON NL4 for passive L SUB 1200 extension
- **Input Sensitivity:** +4dBu at gain centre-notched
- **Pole Mount:** 2 x M20 (K&M)
- **Handles:** 4 x HK Audio MultiGrip
- **Enclosure:** Birch multiplex
- **Grille:** 2mm metal grille backed with black acoustic foam
- **Finish:** Acrylic enamel, black
- **Dimensions:** 380mm x 670mm x 560mm (W x H x D)
- **Weight:** 30.7kg / 67.7lbs

HK Audio Linear L SUB 1200 2 x 10" Passive Subwoofer

- **Power Handling:**
 - **RMS:** 600W
 - **Program:** 1200W
 - **Peak:** 2400W
- **Nominal Impedance:** 8 Ohms
- **Maximum SPL:** 128dB half space (at 10 percent THD)
 - **Peak:** 130dB half space (at 10 percent THD)
- **Sensitivity:** 101dB half space
- **Frequency Response:**
 - **+/-3dB:** 55Hz - X-over
 - **-10dB:** 38Hz - X-over
- **Low-Frequency Speaker:** 2 x 10" with 2.5" voice coil (with advanced cooling technology)
- **Crossover Frequency:** Controller-driven
- **Connections:** 2 x SpeakON NL4
- **Pole Mount:** 2 x M20
- **Handles:** 4 x integrated
- **Enclosure:** Birch multiplex
- **Grille:** 2mm metal grille backed with black acoustic foam
- **Finish:** Acrylic enamel, black
- **Dimensions:** 380mm x 670mm x 560mm (W x H x D)
- **Weight:** 29kg / 63.9lbs