



## DRUMSET-1

Order No.: 23.1390

**Price upon request**

### PRODUCTINFOS

**7-piece drum microphone set,**

consisting of a dynamic bass drum microphone, four dynamic snare drum/tom-tom microphones and two overhead condenser microphones.

- Optimised for sound pickup of drums
- Short-bodied microphones
- Including microphone holder with 16 mm ( $\frac{5}{8}$ " ) tripod socket and 9 mm ( $\frac{3}{8}$ " ) adapter screw for every microphone
- Additional clamps for the snare drum/tom-tom microphones
- Supplied in a practical plastic case

### TECHNICAL SPECIFICATIONS

#### DRUMSET-1

Description                      drum microphones

**DRUMSET-1**

Transmission method	cable
Polar pattern	bi-directional (bass drum) supercardioid (snare drum/tom-tom) cardioid (overhead)
System	dynamic (bass drum) dynamic (snare drum/tom-tom) electret (overhead)
Audio frequency range	50-10,000 Hz (bass drum) 50-15,000 Hz (snare drum/tom-tom) 50-15,000 Hz (overhead)
Nominal impedance	300 $\Omega$ (bass drum) 600 $\Omega$ (snare drum/tom-tom) 6.8 $\Omega$ (overhead)
Sensitivity	1.6 mV/Pa (bass drum) 2.5 mV/Pa (snare drum/tom-tom) 5.6 mV/Pa (overhead)
S/N ratio	66 dB
Max. sound pressure	158 dB (bass drum) 157 dB (snare drum/tom-tom) 161 dB (overhead)
Power supply	DC 48 V, phantom power (overhead)
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 50 mm x 113 mm (bass drum) Ø 40 mm x 93 mm (snare drum/tom-tom) Ø 22 mm x 90 mm (overhead) 430 x 135 x 320 mm (set)
Weight	280 g (bass drum) 199 g (snare drum/tom-tom) 81 g (overhead) 1.5 kg (set)
Connection	XLR, bal.