

dB Technologies SUB 615 Active PA Subwoofer

Specifications

Technical & Acoustic Data

- **Speaker Type:** Active Subwoofer
- **Frequency Response (-10dB):** 42Hz - 124Hz
- **Maximum SPL (1m):** 131dB
- **Directivity:** Omnidirectional
- **LF Driver Diameter:** 15"
- **LF Driver Voice Coil:** 2.5"

Amplifier

- **Amplifier Technology:** SMSP Digital Amplifier
- **Amplifier Class:** Class-D
- **RMS Power:** 600W
- **Peak Power:** 1200W

Processor

- **Controller:** 28/56-Bit DSP
- **Limiter:**
 - Peak
 - Thermal
 - RMS
- **Controls:**
 - Subwoofer Level
 - Outputs Mode
 - Polarity
 - Subwoofer Mode

Connectivity

- **Signal Input:** 2 x XLR (Balanced)
- **Signal Output:** 2 x XLR (Balanced)

Physical Specifications

- **Housing:** Plywood
- **Grille:** Full Metal Grid
- **Pole Mount:** M20
- **Width:** 16.92" / 430mm
- **Height:** 22.83" / 580mm
- **Depth:** 23.62" / 600mm
- **Weight:** 56.22lbs / 25.5kg