

## Specifications

### QSC CP12 Active Speakers

- **Configuration:** Two-Way Active
- **Low Frequency Driver:** 12" Cone Woofer
- **High Frequency Driver:** 1.4" Compression
- **Frequency Response:** 49Hz - 20kHz, -6dB
  - 47Hz - 20kHz, -10dB
- **Sound Pressure Level:** 126dB (Maximum)
- **Nominal Coverage:** 75° Axisymmetric
- **Amplifier Type:** Class-D
- **Amplifier Power:** 1000W (Peak)
- **Input Connectors:**
  - 2 x XLR/TRS Combo (Line and Mic/Line)
  - 1 x 3.5mm TRS Stereo
- **Output Connector:** 1 x XLR (Mix)
- **Controls:**
  - Power
  - 2 x Gain
  - Mic Boost Push Switch
  - 6-Way Contour Selection Switch
- **Indicators:**
  - Power LED
  - 2 x Input Signal LEDs
  - Input B MIC Selected LED
  - Limiter Active LED
- **Power Supply:** 100V - 240V, 50Hz/60Hz
- **Enclosure Material:** Polypropylene
- **Grille:** 18 Gauge Powder Coated Steel
- **Dimensions:** 516mm x 350mm x 323mm / 20.3" x 13.8" x 12.7" (H x W x D)
- **Weight:** 13.7kg / 30.3lbs

### PA Speaker Stands (Pair) With Carry Bag

- **Colour:** Black
- **Material:** Aluminium
- **Dimensions:** 1000mm x 150mm x 150mm
- **Max Load:** 50kg
- **Height Adjustment:** 1000mm - 1800mm
- **Top Hat:** 35mm

## Chauvet DJ GigBAR 2.0 LED Lighting System

- **DMX Channels:** 3, 11 or 23
- **DMX Connectors:** 3-pin XLR
- **Light Source:** (Pars) 6 LEDs (Quad-color RGB+UV) 3.5 W (1.1 A), 50,000 hours life expectancy
- **Light Source:** (Strobe) 4 LEDs (white & UV) 1.8 W (600 mA), 50,000 hours life expectancy
- **Light Source:** (Derby) 6 LEDs (2 red, 2 green, 2 blue) 6 W (1.7 A), 50,000 hours life expectancy, 650nm/100 mW (red) laser diode, 532nm/30 mW (green) laser diode
- **Strobe Rate:** (Strobe) 0 to 18 Hz
- **Beam Angle:** (Pars) 13°, (Strobe) 8°
- **Field Angle:** (Pars) 24°, (Strobe) 18
- **Coverage Angle:** (Laser) 93°, (Derby) 114°
- **Fits Tripod Size:** 37.4 mm
- **Illuminance:** (Pars) 1,205 lux @ 2 m (Per Head), (Strobe) 86 lux @ 2 m (Per Zone)
- **Power Linking:** 8 units @ 120 V; 15 units @ 230 V
- **Input Voltage:** 100 to 240 VAC, 50/60 Hz (Auto-Ranging)
- **Power and Current:** 68 W, 1 A @ 120 V, 60 Hz 64 W, 0.5 A @ 230 V, 50 Hz
- **Weight:** 6.6 kg
- **Size:** 1185 x 110 x 386.5 mm
- **Approvals:** CE, FDA, FCC
- **Stand Height:** 1.5 to 2.5 m
- **Tripod leg width:** 1.2 m
- **Foot Switch Operating Frequency:** 433 MHz
- **Foot Switch Max Unobstructed Distance:** 30.5 m