

Specifications

RCF ART 312-A MK4 Active Speakers Pair with Stands

- **Frequency Response:** 50Hz - 20kHz
- **Maximum SPL:** 128dB at 1m
- **Coverage:** 90° x 60° (H x V)
- **Compression Driver:** 1" diameter (1.5" voice coil)
- **Woofer:** 12" diameter (2.5" voice coil)
- **Input Connector:** XLR, 1/4" jack
- **Input Signal:** Balanced/unbalanced
- **Input Sensitivity:** -2dBu / +4dBu
- **Mic Input Sensitivity:** -32dBu
- **Output Connectors:** XLR
- **Crossover:** 1800Hz
- **Limiter:** Soft limiter
- **Protection:** Thermal, RMS
- **Controls:** Volume, Boost, Mic/Line
- **Total Rated Power:** 400W (RMS) / 800W (peak)
 - **LF Power:** 300W (RMS) / 600W (peak)
 - **HF Power:** 100W (RMS) / 200W (peak)
- **Cooling:** Convection
- **Connections:** VDE
- **Cabinet:**
 - **Material:** PP composite
 - **Grille:** Steel
 - **Colour:** Black
 - **Mounting Hardware:** 4 x M10
 - **Pole Mount Receptacle:** Yes
 - **Handles:** 1 x top, 2 x side
- **Dimensions:** 680mm x 405mm x 345mm / 26.77" x 15.94" x 13.58" (H x W x D)
- **Weight:** 16.8kg / 37.04lbs

Specifications

Chauvet DJ GigBAR 2.0 LED Lighting System

- **DMX Channels:** 3, 11 or 23
- **DMX Connectors:** 3-pin XLR
- **Light Source:** (Pars) 6 LEDs (Quad-color RGB+UV) 3.5 W (1.1 A), 50,000 hours life expectancy
- **Light Source:** (Strobe) 4 LEDs (white & UV) 1.8 W (600 mA), 50,000 hours life expectancy
- **Light Source:** (Derby) 6 LEDs (2 red, 2 green, 2 blue) 6 W (1.7 A), 50,000 hours life expectancy, 650nm/100 mW (red) laser diode, 532nm/30 mW (green) laser diode
- **Strobe Rate:** (Strobe) 0 to 18 Hz
- **Beam Angle:** (Pars) 13°, (Strobe) 8°
- **Field Angle:** (Pars) 24°, (Strobe) 18°
- **Coverage Angle:** (Laser) 93°, (Derby) 114°
- **Fits Tripod Size:** 37.4 mm
- **Illuminance:** (Pars) 1,205 lux @ 2 m (Per Head), (Strobe) 86 lux @ 2 m (Per Zone)
- **Power Linking:** 8 units @ 120 V; 15 units @ 230 V
- **Input Voltage:** 100 to 240 VAC, 50/60 Hz (Auto-Ranging)

- **Power and Current:** 68 W, 1 A @ 120 V, 60 Hz 64 W, 0.5 A @ 230 V, 50 Hz
- **Weight:** 6.6 kg
- **Size:** 1185 x 110 x 386.5 mm
- **Approvals:** CE, FDA, FCC
- **Stand Height:** 1.5 to 2.5 m
- **Tripod leg width:** 1.2 m
- **Foot Switch Operating Frequency:** 433 MHz
- **Foot Switch Max Unobstructed Distance:** 30.5 m