

dB Technologies 1.2 kW Medium Disco PA System Specifications

dB Technologies SUB 05 D 15" 400W Active Subwoofer

Technical Data

- **Speaker Type:** Active Bandpass Subwoofer

Acoustical Data

- **Frequency Response [-10dB]:** 30 - 150Hz
- **Max SPL:** 129 dB
- **Directivity:** Omnidirectional
- **LF:** 15"

Amplifier

- **Amp Technology:** digipro
- **Amp Class:** Class D
- **Power PRG:** 800 W
- **Cooling:** Convection

Processor

- **Controller:** DSP 24bit/48kHz
- **Phase:** 0, 180 Degrees
- **Limiter:** Dual Active
- **Delay Option:** No
- **Crossover Frequency LF-MF:** 2 Setups Hz
- **Slope LF-MF:** 24 dB/Octave

Input Selection

- **Signal Input:** 2x XLR
- **Microphone Input:** Yes
- **Signal Output:** 2x XLR Link Out/ X-Over Out
- **Power Socket:** VDE
- **Voltage Range:** 240 V

Physical Specifications

- **Housing:** H.E.T
- **Housing Design:** Square
- **Colour:** Black
- **Surface Texture:** Textured Acrylic Lacquer
- **Castors:** No
- **Handles:** 1 Per Side
- **Pole Mount:** 1 x 36mm, Top
- **Front Grille:** Wooden

Dimensions

- **Width:** 490mm
- **Height:** 515mm
- **Depth:** 610mm
- **Weight:** 31.8kg

dB Technologies Cromo 10+ Active PA Speaker

Technical Data

- **Speaker Type:** 2-Way Active Speaker

Acoustical Data

- **Frequency Response [-10dB]:** 65 - 20.000 Hz
- **Frequency Response [+/- 3dB]:** 70 - 19.000 Hz
- **Max SPL:** 121 dB
- **HF:** 1"
- **Directivity:** 90/70 x 60 degrees
- **Horn:** Asymmetrical CD Horn
- **LF:** 10"

Amplifier

- **Amp Class:** Class D
- **Power PRG:** 400 W
- **Cooling:** Convection

Processor

- **Controller:** DSP 24bit/48kHz
- **Limiter:** Dual Active Peak, RMS, Thermal
- **Crossover Frequency MF-HF:** 2000 Hz
- **Slope MF-HF:** 24dB/Octave

Input Selection

- **Signal Input:** 1x XLR, 1x 6.3mm Phone Jack
- **Input Sensitivity [dBu]:** -40 dBu
- **Microphone Input:** Yes
- **Power Socket:** VDE

Physical Specifications

- **Housing:** Polypropylen PP
- **Housing Design:** Multifunctional
- **Colour:** Black
- **Handles:** 1, Top
- **Pole Mount:** 36mm
- **Angles Up:** Monitor use 43 degrees
- **Front Grille:** Metal, 1.2mm

Dimensions

- **Width:** 320mm
- **Height:** 508mm
- **Depth:** 297mm
- **Weight:** 12

PA Speaker Stands (Pair) With Carry Bag

- **Colour:** Black
- **Material:** Aluminium
- **Dimensions:** 1000mm x 150mm x 150mm
- **Max Load:** 50kg
- **Height Adjustment:** 1000mm - 1800mm
- **Top Hat:** 35mm

XLR (F) - XLR (M) Pro Mic Cable, 3m and 6m

- 7mm cable
- PVC Jacket
- PVC Insulation
- 16 x 6 x 0.12mm braided shield
- Conductive PE shield
- 20 x 0.12mm conductors
- Colour: Black