BassCube₂

reference level



The BassCube 2 has proven to do an excellent job to reproduce double bass authentically.

Well balanced analogue sound design covers the ranges gently and proportionately so that tone always stays clear, crisp and transparent yet powerful and defined without any stress!

Its **two channels** are equally equipped and allow two different instruments set up in all comfort – and be sure it works very well for electric bass too.

Whether 'arco' or 'pizzicato' – the BassCube 2 sounds like your bass: round and open – you can hear the stroke of your bow as true to life as the placing of your fingers on the fingerboard.

- 550 watts, dynamic control
- Two-way coaxial neodymium speaker system, 12" bass plus 1" HF driver
- Twin-channel 2-way acoustic system
- Compressor and selectable input stage
- 20,00 kg (44.00 lbs)

Inputs	
channels 1, 2	Combo socket XLR + 6.3 mm (1/4") input jack socket as high impedance unbalanced jack input fr instruments, line-level and mic-mode sources. (To addressed by mode switch: piezo, line, 9 V, mic, 48\

Tone Contols	
equalizer	three band tone controls for both channels
colour	'mid-cut-treble-boost'-filter
effect	Compressor with ratio and threshold, notch filter with frequency, level and bandwidth switch.
Power	

power amp	550 W / 8 ohms, dynamic control
analog signal	subsonic filter, low distortion
processing	RMS limiter

Two-way coaxial	neodymium speaker system,
	12" bass plus 1" HF driver

crossover fc = 3.9 kHz, 12dB / oct.

Features

Speaker Systems

adjustable DI-master, DI-channel 1 and 2, aux in, aux out, monitor, tuner, line out, subbass headphones insert master, insert channel 1 and 2, footswitch (mute channels and switch solo/ensemble) ground lift

Accessoiries	
footswitch (mute channels and switch solo/ensemble), ground lift $$	
line out, subbass headphones insert master, insert channel 1 and 2	

	softcover
Specifications	
cabinet	18 mm (0.70") finnish birch plywood
finish	waterbased acrylic, black spatter finish
dimensions	400 mm x 400 mm x 365 mm (15.70" x 15.70" x 14.00"), HxWxD
weight	20,00 kg (44.00 lbs)
Can be combined with:	

AS 550/D sub

