

STAGESOURCE L2m

Compact, 2-Way Powered PA Speaker with Studio-Quality Sound

Optimize your sound for any application with DSP-powered performance modes

800 watts of power and articulation, from the coffee house to the club

Protect your performance with precision feedback suppression

Streamline setup with L6 LINK™ digital networking

StageSource® L2m loudspeakers use massive DSP—unmatched in their class—and huge power to deliver studio-quality live sound at every gig. Onboard sensors get you set up fast, and built-in feedback suppression keeps your sound pure throughout your performance. When you need to build a larger system, onboard L6 LINK™ digital networking communicates with additional speakers for seamless setup and optimal sound. StageSource is the only speaker that is designed to be the perfect solution for all your live sound applications—from coffee shops to major clubs.

Specifications

Part Number
99-032-0225
UPC
614252299954
Case Pack
1
Case Pack Size
28.9" H x 17.2" W x 17.2" L

_	Case Pack Weight
Ę	50 lbs
	Display Box Size
2	28.9" H x 17.2" W x 17.2" L
Display Box Weight	
E	50 lbs







Smart Speaker modes for main PA, personal PA, floor monitor, instrument backline and more

Digital networking via L6 LINK™

Multi-function, modular architecture for true scalability

On-board accelerometer for sound optimization in horizontal or vertical applications

12-band feedback suppression

800-watt, 2-way, bi-amped speaker system

Direct radiator design with 1" Exit HF compression driver

128dB Max SPL

100° horizontal x 50° vertical coverage

M10 suspension points

Heavy-duty, tour-grade plywood construction





Back Panel

