



Bowers & Wilkins

607 S3

Technical Information



Technical features

Decoupled Double Dome Titanium tweeter
Continuum™ cone bass / midrange
Flowport™

Description

2-way vented-box system

Drive units

1x ø25mm (1 in) Titanium Dome high-frequency
1x ø130mm (5 in) Continuum cone bass / midrange

Frequency range

-6dB 40Hz - 33kHz

Frequency response

(+/-3dB from reference axis)

52Hz - 28kHz ±3dB

Sensitivity

(on axis at 2.83Vrms at 1m)

84dB

Harmonic distortion

2nd and 3rd harmonics (90dB, 1m on axis)
<1% 100Hz - 22kHz
<0.5% 500Hz - 10kHz

Nominal impedance

8Ω (minimum 3.0Ω)

Recommended amplifier power

30W - 100W into 8Ω on unclipped programme

Max. recommended cable impedance

0.1Ω

Dimensions

Height: 300 mm (11.8 in) cabinet only
Width: 165 mm (6.5 in) cabinet only
Depth: 207 mm (8.2 in) cabinet only
235 mm (9.3 in) including grille and terminals

Net weight

4.65kg (10.3lbs)

Finishes

Cabinet: Black
White
Oak
Grille: Black (Black)
Grey (White and Oak)